

Chair 4 stars swivel base with feet

Shell: recyclable polypropylene reinforced with fiberglass

Upholstered options: polypropylene shell with frontal upholstery, seat cushion only or fully upholstered (seat height + 4 cm.)

Covers: fabric, faux-leather or C.O.M. (preferably in solid colour)

Base: die-cast aluminium frame available in powder coated or brushed finish

Feet: thermoplastic material



Chair	Article	Finish / Upholstery	Powder coated base	Polished brushed (67) base	pcs / dimensions volume / gross weight product net weight
Polypropylene	R0100	Polypropylene			1 pc / 49x58x85,5 cm 0,24 m ³ / 8,4 Kg 6,2 Kg
Polypropylene with frontal upholstery	R0101	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,24 m ³ / 10,4 Kg 8 Kg
Polypropylene with seat cushion only	R0102	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,24 m ³ / 9,4 Kg 7 Kg
Fully Upholstered	R0103	Gazebo Xtreme Plus / Magnum / Rivet / Main Line Flax Blazer / Gingko / Step Melange / Silvertex / Remix3 Steelcut Trio3 / Atlas / Canvas2 C.O.M. (solid colour)			1 pc / 49x58x85,5 cm cm 0,24 m ³ / 10,8Kg 8,4 Kg


Fire-retardant version

Fire-retardant version black colour 7F


Fire retardant compounds may cause slightly difference of colours

Finishes

Polypropylene




Metal frame



Dimensions

Art. R0100



Customer's own material

For customer's own material, the form at the end of the price list shall apply, to be sent to Segis Spa with the Client's signature.

Solid fabric:

for 1 pc seat and back (H. 140 cm ca) 65 cm

for 1 pc seat only (H. 140 cm ca) 40 cm

for 1 pc fully upholstered (H.140 cm ca) 120 cm

Fire retardant certifications

Art. R0100 meets Class 2 Standards by the Italian Minister of Interior.

Resistance tests

R0100

EN 16139 :2013 4.1 - General requirements

EN 16139 :2013 4.2.1 - Shear and squeeze points when setting up and folding

EN 16139 :2013 4.2.3 - Shear and squeeze point during use

EN 16139 :2013 4.3.1 - General

EN 16139 :2013 4.3.2 - Swiveling chairs

EN 16139 :2013 4.5 - Safety of the construction

EN 16139 :2013 5 - Safety, strength and durability requirements

EN 16139 :2013 6 - Test methods

BS EN 1728:2012 6.4 - Seat and back static load test

BS EN 1728:2012 6.5 - Seat front edge static load test

BS EN 1728:2012 6.6 - Vertical static load on back

BS EN 1728:2012 6.15 - Leg forward static load test

BS EN 1728:2012 6.16 - Leg sideways static load test

BS EN 1728:2012 6.17 - Combine seat and back durability test

BS EN 1728:2012 6.18 - Seat front edge durability test

BS EN 1728:2012 6.24 - Seat impact test

BS EN 1728:2012 6.28 - Backward fall test